

# AccuMark TTO Series

Thermal Transfer Overprinters



Accutek's AccuMark TTO Series Coders are smart Thermal Transfer Overprinters. Accutek's AccuMark TTO Series Coders can print everything from simple date codes and batch codes to logos, product descriptions, ingredients lists, nutritional panels and fully compliant barcodes.

Thermal Transfer Overprinters (TTO) use high-resolution thermal printheads to print crisp, clear date codes, lot numbers, bar codes, text, and graphics onto flexible packaging films and labels.

The Thermal Transfer Overprinters thermal printhead transfers ink on a ribbon onto various substrates including label stock, plastic films, flat packaging, plastic and foil. The printheads are in direct contact with the substrate which gives you better quality text, graphics, and barcodes.

A thermal transfer printer also is a best option for those who need to print high-density codes and labels with longevity on fast moving production lines.

## ***Key Features:***

- Print on most packaging film/Label
- Super excellent adhesive which suitable for high print requirements

## ***Options:***

- Ask about different Color options

# AccuMark TTO Series

Thermal Transfer Overprinters

## Model: 48-TTO-A32

### Unit Specifications

<b>Dimensions (LxWxH):</b>	Print Unit: 188x190x180 - Controller Box: 175x235x110
<b>Weight:</b>	Print Unit: 8.5KG - Controller Box: 2.0 KG
<b>Print Head:</b>	32mm, 300dpi (12points/mm)
<b>Print Area:</b>	32mmx60mm
<b>Print Mode:</b>	Print at fixed speed
<b>Print Frequency:</b>	300times/min
<b>Max Length of Ribbon:</b>	500m
<b>Width of Ribbon:</b>	22mm~33m
<b>Interface:</b>	USB,RS232,Network Interface
<b>Electrical Requirements:</b>	200W
<b>Environmental operating temperature:</b>	0~40°C
<b>Relative Humidity:</b>	10%~95% (Non Condensing)
<b>Air Supply:</b>	6bar/90psi(max).dry, clean

## Model: 48-TTO-A53

### Unit Specifications

<b>Dimensions (LxWxH):</b>	Print Unit: 210x210x180 - Controller Box: 175x235x110
<b>Weight:</b>	Print Unit: 9.5KG - Controller Box: 2.0 KG
<b>Print Head:</b>	53mm, 300dpi (12points/mm)
<b>Print Area:</b>	53mmx70mm
<b>Print Mode:</b>	Print at fixed speed
<b>Print Frequency:</b>	300times/min
<b>Max Length of Ribbon:</b>	600m
<b>Width of Ribbon:</b>	35mm~55m
<b>Interface:</b>	USB,RS232,Network Interface
<b>Electrical Requirements:</b>	200W
<b>Environmental operating temperature:</b>	0~40°C
<b>Relative Humidity:</b>	10%~95% (Non Condensing)
<b>Air Supply:</b>	6bar/90psi(max).dry, clean

