

Auto Induction Sealer

Automatic Induction Sealing System

Key Features:

- High efficiency power use
- Highly accurate
- Easy to setup
- Water cooled
- Food grade stainless steel construction
- Over 4 Kw of power for large mouth caps
- Up to 120mm caps
- Small profile with a C-Frame design
- Casters or leveling feet

Optional Features:

- Deep well cap path
- Powered conveyor

The Solid State 4kw Induction Generator is housed in a sanitary stainless steel splashproof enclosure 400 x 400 x 200mm with all controls mounted behind a window with a lockable door. Facilities are provided for interlocking the availability of output power with conveyor movement and a flashing beacon functions if a fault condition occurs. The standard Induction Sealing Head is able to cover a wide range of closure designs and diameters up to 120mm. The sealing head is dimensioned in relation to the conveyor speed and other factors to optimize the sealing conditions.

In addition, the sealing head mounting is adjustable, including the ability to 'skew' which enables exposure times to be reduced if necessary as well as achieving a more uniform heat pattern for larger closures. This versatile, self-contained and compact equipment, including Induction Sealer and water cooler/recirculator, operates from a single phase 200/240V 12A 60Hz supply.



2980 Scott St, Vista CA 92081 • 760.734.4177 • Fax 760.734.4188

Email: sales@accutekpackaging.com • accutekpackaging.com

ACCUTEK
Packaging Equipment Companies, Inc.